

Code ST05	Project E04-A	Release C	TECHNICAL DATASHEET
---------------------	-------------------------	---------------------	----------------------------

ELECTRICAL CONNECTIONS

Encoder supplied with M23 (12 Pin) connector

CONNECTION				
N. Pin	Signals (BE, SB, SG)	Signals (SC, BV)	Signals (SP)	Signals (SR, SH)
1	0 V (supply voltage)	0 V (supply voltage)	Clock	0 V (supply voltage)
2	Data	Data	Clock	Data
3	Clock	Clock	Data	Clock
4	n.c.	A	Data	n.c.
5	Direction *	Direction *	RS 232 TxD	Direction **
6	n.c.	B	RS 232 RxD	n.c.
7	n.c.	A	0 V (signal output)	n.c.
8	+ V	+ V	Direction	+ V
9	n.c.	B	Preset 1	n.c.
10	Data	Data	Preset 2	Data
11	Clock	Clock	+ V	Clock
12	0 V (signal output)	0 V (signal output)	0 V (supply voltage)	Preset **


Encoder supplied with M12 (8 Pin) connector

CONNECTION	
N. Pin	Signals (BE, SB, SG)
1	+ V
2	0 V
3	n.c.
4	Clock
5	Data
6	Clock
7	Direction *
8	Data

* Not connected = ascending code values with clockwise rotation
 Connected to 0 V = descending code values with clockwise rotation

** Preset and Direction active with signal high

DIMENSIONS



WHAT TO AVOID

- Any mechanical working (cutting, drilling, milling, etc.).
- Any modification of the encoder body or shaft.
- Any improper use, not complying with the technical instructions provided by the Manufacturer.
- External shocks or stresses.

